

**TECHNICAL SPECIFICATIONS**

<b>TYPE</b>	P.110-8008M PANAMA
<b>APPLICATION AREAS</b>	Tents, awnings, cover sheets, playgrounds, truck tarpaulins
<b>PROPERTIES</b>	WATER PROOF - LIGHT PROOF - FLAME RETERDAND - UV PROTECTION
<b>BASE FABRIC</b>	PES / High resistant Super Low shrinkage
<b>CONTEXTURE OF YARN</b>	1100 dtex 2:2 ( DOUBLE WEAVING)
<b>WARP / WEFT</b>	12*12 ( 6x2 *6x2 )
<b>WEIGHT</b>	800 gr/sqm
<b>WIDTH</b>	1500 mm- 3000 mm
<b>ROLL LENGTH</b>	40 mt - 50 mt
<b>FINISH</b>	GLOSSY / MATT EMBOSSED
<b>TENSILE STRENGTH</b>	3500/4000 N/5 cm
<b>TEAR RESISTANCE</b>	500 N
<b>ADHESION</b>	80
<b>ABRASION</b>	> 20.000 (revs)
<b>WATERPROOFING</b>	8000 mmss
<b>COLOUR FASTNESS</b>	8
<b>HANDLING TEMPERATURE RANGE</b>	( - 30°C / + 70°C )
<b>QUALITY MANAGEMENT SYSTEM</b>	TSE ISO 9001 Compliance with ( DIN ) EN 12641-1 Compliance with ( DIN ) EN 12641-2